

## Specifications

---

STYLE NAME	<b>SWIFT MODULAR</b>
CONSTRUCTION	Tufted Multi-Level Textured Loop
PILE CONTENT	100% B.C.F. Synthetic Fiber
DYE METHOD	Solution Dyed
GAUGE	1/10
PILE HEIGHT	4.5mm ± 5%
TOTAL THICKNESS	7.5mm ± 5%
PILE WEIGHT	650 gm/m <sup>2</sup> ± 5%
TOTAL WEIGHT	4300 gm/m <sup>2</sup> ± 5%
BACKING MATERIAL	PVC with Fibreglass Reinforcement
TILE SIZE	50 cm x 50 cm
TILES PER BOX	20 pcs

## Performance

---

FLOOR RADIANT PANEL	ASTM E-648
DIMENSION STABILITY	AACHEN Test & CNS 13924 $\pm$ 0.2%
FLAMMABILITY	BS 4790-1987: Hot Metal Nut, Method 1 Pass
LIGHT COLORFASTNESS	BS 1006 B02-1990, Grade 5 Pass
CROCKING COLORFASTNESS	BS EN ISO 105 X 12-1995 Pass
ELECTROSTATIC PROPENSITY	CNS 13595 10 $\pm$ 2.0KV 20% R.H.,70F
SOIL RESISTANCE	3M Test Pass

All specifications are subject to normal manufacturing tolerances.

Recommended Installation Methods:

