

# Specifications

---

STYLE NAME	<b>X-FACTOR MODULAR</b>
CONSTRUCTION	Tufted Loop Pile
PILE CONTENT	100% B.C.F. Synthetic Fiber
DYE METHOD	Solution Dyed
GAUGE	1/10
PILE HEIGHT	4.0 mm ± 5%
TOTAL THICKNESS	7.0 mm ± 5%
PILE WEIGHT	780 gm/m <sup>2</sup> ± 5%
TOTAL WEIGHT	4300 gm/m <sup>2</sup> ± 5%
BACKING MATERIAL	PVC with Fibreglass Reinforcement
TILE SIZE	50 cm x 50 cm
TILES PER BOX	20 pcs


# Performance

---


SOIL RESISTANCE	3M Test Method 8 of 10 Pass
DIMENSION STABILITY	CNS 13924 & AACHENTEST $\square \pm 0.2\%$
FLAMMABILITY	CNS 13592 3.5 After Flame : Within 20 Seconds Charred Area : Within 10 cm
LIGHT COLORFASTNESS	CNS 13592 3.4 & AATCC 16E $\square 4.0$
CROCKING COLORFASTNESS	CNS 13592 3.4 & AATCC 165 $\square 4.0$
ELECTROSTATIC PROPENSITY	CNS 13595 10 $\square 2.0KV$ 20% R.H.,70F

All specifications are subject to normal manufacturing tolerances.


Recommended Installation Methods:



Monolithic



Ashlar or Brick



Quarter-turn

