


# WALLFLEX

(2mm x 1.5m x 20m)




All Wallflex colours now available as 2.0mm




NEUTRAL WHITE  
LRV: 77.10

6W608229




COOL WHITE  
LRV: 78.89

6W608249




DOVE WHITE  
LRV: 74.75

6W608079




ALABASTER  
LRV: 79.05

6W608469




LINEN  
LRV: 70.94

6W608289




ICE WHITE  
LRV: 80.00

6W608189




BLUE GREY  
LRV: 63.01

6W608219




ALOE  
LRV: 65.05

6W608309



MUSHROOM  
LRV: 65.01

6W608269



PARADISE

6W608299

LRV: 56.51



Variations may occur between photographic images, samples and batches in terms of colour, shade, pattern or similar.



Lady Cilento Children's Hospital, Brisbane







Infinity Custom allows you to create your own customised flooring and walling products based on our Accolade and Wallflex formulations\*



\*Minimum order quantities apply. Contact your Sales Representative or call 1800 632 624 for more information.









Lady Cilento Children's Hospital, Brisbane





	ACCOLADE PLUS	ACCOLADE FOOHOLD	ACCOLADE SAFE	WALLFLEX
Practical	<ul style="list-style-type: none"> <li>Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor.</li> <li>Protective polyurethane finish reduces initial and ongoing maintenance and increases scuff resistance.</li> </ul>	<ul style="list-style-type: none"> <li>Polyurethane reinforced surface featuring PUR<sup>2</sup> technology to aid maintenance and provide additional resistance against staining.</li> <li>Exclusive homogeneous formulation including replenishing polyurethane throughout the thickness of the floor.</li> <li>Colours mix and match with Accolade Safe &amp; Accolade Plus.</li> </ul>	<ul style="list-style-type: none"> <li>Offers supreme safety without the impregnated silicon chips of conventional non-slip resistant flooring that can attract and hold dirt, increasing maintenance and wear and tear on cleaning equipment.</li> <li>Unique construction with highly accented jaspe (multi-colour chip) visual helps mask dirt and wear patterns.</li> </ul>	<ul style="list-style-type: none"> <li>Polyurethane coating aids maintenance.</li> <li>Clean, simple design for an uncomplicated look or the addition of a frieze if desired.</li> <li>1.5 metre width ideal dado height for ease of installation.</li> <li>2.0mm to align with floor vinyl.</li> </ul>
Durable	<ul style="list-style-type: none"> <li>Homogeneous construction for excellent dent and gouge resistance.</li> <li>The embossed surface texture and highly accented jaspe (multi-colour chip) visual help hide dirt and wear patterns created in high traffic conditions.</li> </ul>	<ul style="list-style-type: none"> <li>Combination of embossed surface, aluminium oxide and polyurethane provides added slip resistance and protects long term appearance.</li> <li>Homogeneous construction for excellent durability and indentation resistance.</li> </ul>	<ul style="list-style-type: none"> <li>The embossed surface reduces aquaplaning, while aiding slip resistance.</li> </ul>	<ul style="list-style-type: none"> <li>Polyurethane coating reduces maintenance costs and protects long term appearance.</li> <li>Homogeneous construction for excellent dent and gouge resistance.</li> <li>2.0mm thick for improved indent resistance.</li> </ul>
Applications	<ul style="list-style-type: none"> <li>Hospital</li> <li>Aged Care</li> <li>Health Care</li> <li>Education</li> <li>Light Industrial</li> <li>Mercantile</li> <li>Hospitality</li> </ul>	Recommended for wet barefoot areas of <ul style="list-style-type: none"> <li>Hospital</li> <li>Aged Care</li> <li>Health Care</li> <li>Education</li> </ul>	<ul style="list-style-type: none"> <li>Hospital</li> <li>Aged Care</li> <li>Health Care</li> <li>Education</li> <li>Light Industrial</li> <li>Mercantile</li> <li>Hospitality</li> </ul>	<ul style="list-style-type: none"> <li>Hospital</li> <li>Aged Care</li> <li>Health Care</li> <li>Education</li> <li>Light Industrial</li> <li>Mercantile</li> <li>Hospitality</li> </ul>

PLEASE NOTE: Recommendations are for guidance only, refer to relevant local, state and federal construction codes and standards for requirements

TECHNICAL DATA		ACCOLADE PLUS	ACCOLADE FOOHOLD	ACCOLADE SAFE	WALLFLEX
Type of floor covering/wall covering	ISO 10581	Homogeneous sheet vinyl	Homogeneous sheet vinyl	Homogeneous sheet vinyl	Homogeneous sheet vinyl
Manufactured in		Australia	Australia	Australia	Australia
Overall Thickness	ISO 24346	2.0mm	2.0mm	2.0mm	2.0mm
Wear Layer thickness	ISO 24340	2.0mm	2.0mm	2.0mm	2.0mm
Roll dimensions	ISO 24341	1.83m x 16m	1.83m x 16m	1.83m x 16m	1.5m x 20m
Polyurethane Reinforced		Yes PUR	Yes PUR	No	Yes PUR
Binder Content	ISO 10581	Type 1	Type 1	Type 1	Type 2
Wear resistance	EN 660-2	Group T	Group P	Group P	N/A
Slip Resistance	AS 4586				
Appendix A: Wet pendulum		P3*	P4	P4*	N/A
Appendix C: Wet/barefoot			B*	B*	
Appendix D: Oil-wet		R10*	R11*	R10*	
Fire Resistance (Flooring)	ISO 9239-1				
Critical Radiant Flux		≥8kW/m <sup>2</sup>	≥8kW/m <sup>2</sup>	≥8kW/m <sup>2</sup>	N/A
Smoke Development Rate		≤750%. minutes	≤750%. minutes	≤750%. minutes	
Fire Resistance (Walling)	AS/NZS 3837				
Cone Calorimeter		Group 3	Group 3	Group 3	Group 1
Average specific extinction area		<250m <sup>2</sup> /kg	<250m <sup>2</sup> /kg	<250m <sup>2</sup> /kg	<250m <sup>2</sup> /kg
Classification (Use Area)	ISO 10874	Commercial: 34  Light Industrial: 43 	Commercial: 34  Light Industrial: 43 	Commercial: 34  Light Industrial: 43 	N/A


PLEASE NOTE: For Infinity & Infinity Custom minimum order quantities apply. Contact your Sales Representative or call 1800 632 624 for more information.

\*For details refer to individual third party certificates.



Visit [www.armstrongflooring.com.au](http://www.armstrongflooring.com.au) or contact Customer Service 1800 632 624 for technical data, installation, cleaning and maintenance instructions.

Contact:



**Armstrong Flooring Pty Ltd**  
29 – 39 Mills Road, Braeside, 3195 Victoria Australia

For further information and samples:  
Australia Freecall 1800 632 624  
Email [customer\\_services@armstrongflooring.com](mailto:customer_services@armstrongflooring.com) or contact us on the web

[www.armstrongflooring.com.au](http://www.armstrongflooring.com.au)