

Specification

Linoleum xf

Linoleum homogeneous floorcovering on jute backing for rolls and synthetic backing for tiles.
 Composition: Wood and cork flour, linseed oil, natural resins, pigments.
 Product standard: EN 548.

CERTIFICATION & CLASSIFICATION	STANDARDS	Veneto xf	Veneto Acoustic xf	Veneto Tiles xf	Silencio xf	Allegro xf	Etrusco xf
Type of floorcovering	EN 686 EN 687			Linoleum on a corkment backing		Linoleum on a foam backing	
CE Certification	EN 14041	Yes	Yes	Yes	Yes	Yes	Yes
Classification UPEC		U2SP2E1C2	U4P3E1/2C2	U4P3E1/2C2		U4P3E1/2C2	U4P3E1/2C2
Classification	EN 685	Classes:	Classes:	Classes:	Classes:	Classes:	Classes:
	Domestic	23	23	23	23	23	23
	Commercial	32	34	34	33	34	34
	Light industrial	41	42	42	41	42	42
TECHNICAL CHARACTERISTICS	STANDARDS	Veneto xf	Veneto Acoustic xf	Veneto Tiles xf	Silencio xf	Allegro xf	Etrusco xf
Surface Treatment		xf surface	xf surface	xf surface	xf surface	xf surface	xf surface
Total thickness	EN 428	2.0 mm	2.5 mm	3.2 mm	4.0 mm	2.5 mm	3.8 mm
Total weight	EN 430	ca. 2 400 g/m ²	ca. 3 000 g/m ²	ca. 3 900 g/m ²	ca. 4 500 g/m ²	ca. 3 150 g/m ²	ca. 3 350 g/m ²
Residual indentation	EN 433	ca. 0.07 mm	ca. 0.08 mm	ca. 0.10 mm	ca. 0.25 mm	ca. 0.08 mm	ca. 0.08 mm
Flexibility	EN 435 Method A	≤ 25 mm Ø	≤ 30 mm Ø	≤ 40 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø	≤ 30 mm Ø
Form of delivery	EN 426 (rolls)		≤ 30 lm x 2 m		≤ 27 lm x 2 m		≤ 27 lm x 2 m
	EN 427 (Tiles) • Side length • Squareness and straightness				50 x 50 cm deviation: ≤ 0.50 mm deviation: ≤ 0.35 mm		
TECHNICAL PERFORMANCES	STANDARDS	Veneto xf	Veneto Acoustic xf	Veneto Tiles xf	Silencio xf	Allegro xf	Etrusco xf
Dimensional stability	EN 434					Variation ≤ 0.10 %	
Fire classification	EN 13501-1	C _f s1	C _f s1	C _f s1	C _f s1	C _f s1	C _f s1
Impact sound reduction	ISO 140-8 EN ISO 717-2	5 dB	6 dB	9 dB	14 dB	6 dB	6 dB
Impact sound reduction with Elafono*	ISO 140-8 EN ISO 717-2	14 dB	15 dB	15 dB		15 dB	15 dB
Castor chair	EN 425	Suitable for office chairs with castors type W (Norm EN 12529)					
Cigarette burns	EN 1399	Resistant to cigarette burns.					
Static electrical propensity	EN 1815	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV	< 2 kV
Chemical resistance	EN 423	Resistant to dilute acids, oils, fats, current solvents and alkalis.					
Thermal resistance Underfloor heating	EN 12524	0.012 m ² K/W Suitable	0.015 m ² K/W Suitable	0.019 m ² K/W Suitable	0.040 m ² K/W Suitable	0.015 m ² K/W Suitable	0.015 m ² K/W Suitable
Light fastness	ISO 105-B02 Method 3	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6	≥ 6
Colours		50	50	6	on request	on request	17


The above information is subject to modification for the benefit of further improvement. (02/10).

CUSTOMS TARIFF : 482050000000F

To obtain the exact colour of the samples in this card, it is recommended to expose them to sunlight for several hours in order to remove the normal yellowing effect due to the oxydation process. Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

***Elafono :**

Description : one-layer underlayer made of cork grain and a binding agent on jute backing.
 Properties: sound reducing effect. Available : rolls ≤ 30 lm x 2 m. Thickness: 2.0 mm



Australia: Tarkett Australia Pty Ltd - Tel. +61 2 96 34 73 73 • **Austria:** Tarkett Holding GmbH, Niederlassung Wien - Tel. +43 1 478 80 62 • **Baltic States:** Tarkett Wyk_adziny Sp. z o.o. - Tel. +370 37 262 220 • **Belgium:** Tarkett France Belux - Tel. +32 16 35 98 80 • **Brazil:** Tarkett FADEMAC - Tel. +55 12 3954 7244 • **Canada:** Tarkett Inc. - Tel. +1 450 293 173 • **China:** Tarkett Asia Pacific Limited - Shanghai Representative Office - Tel. +86 21 60 95 6838 / +86 21 6095 6859 • **Czech Republic:** Tarkett SAS, org. slozka - Tel. +420 271 001 602 • **Denmark:** Tarkett A/S - Tel. +45 43 90 60 11 • **Finland:** Tarkett Oy - Tel. +358 9 5406 5870 • **France:** Tarkett France - Tel. +33 1 41 20 42 49 • **Germany:** Tarkett Holding GmbH, Bereich Objekt - Tel. +49 (0) 62 33 810 • **Greece:** Tarkett Monoprosopi Ltd - Tel. +30 2 10 576 3889 • **Hong Kong:** Tarkett Asia Pacific Ltd. - Tel. +852 251 18 716 • **Hungary:** Tarkett SAS - Tel. +36 1 437 8150 • **Italy:** Tarkett S.p.A. - Tel. +39 02 893 411 • **Luxembourg:** Tel. +352 949 211 8804 • **Middle East:** Tarkett Middle East - Tel. +961 151 3363/4 • **Netherlands:** Tarkett Holding GmbH - Vestiging Nederland - Tel. +31 76 57 80 760 • **Norway:** Tarkett AS - Tel. +47 32 20 92 00 • **Poland:** Tarkett Wyk_adziny Sp. z o.o. - Tel. +48 22 639 31 66 • **Portugal:** Tarkett SA - Tel. +351 21 427 64 20 • **Russian Federation:** Tarkett Russia - Tel. +7 4 95 777 69 83 • **Slovakia:** Tarkett SAS - Tel. +421 248 291 317 • **Singapore:** Tarkett Far East - Tel. +65 67 43 53 84 • **South East Europe:** Tarkett Trade d.o.o. - Tel. +381 21 7557 649 • **Spain:** Tarkett Floors S.L - Tel. +34 91 358 00 35 • **Sweden:** Tarkett Sverige AB - Tel. +46 771 25 19 00 • **Switzerland:** Tarkett Holding GmbH, Bereich Objekt Schweiz - Tel. +41 (0) 43 233 79 24 • **Turkey:** Tarkett ASPEN - Tel. +90 212 213 65 80 • **Ukraine:** Tarkett UA - Tel. +380 (44) 569 12 21 • **United Kingdom:** Tarkett Ltd - Tel. +44 (0) 1622 854 040 • **North America:** Johnsonite - Tel. +1 440 543 8916 • Tarkett Inc. USA - Tel. +1 713 869 5811 • **Latin America:** Tarkett FADEMAC - Tel. +55 12 3954 7244 • **Tarkett International:** Tel. +33 1 41 20 41 01