

# Specifications

---

STYLE NAME	<b>BARCODE MODULAR</b>
CONSTRUCTION	Tufted Loop Pile
PILE CONTENT	100% B.C.F. Synthetic Fiber
DYE METHOD	Solution Dyed
GAUGE	1/10
PILE HEIGHT	5.0mm (0.174 Inch) ± 5%
TOTAL THICKNESS	7.0mm (0.276 Inch) ± 5%
PILE WEIGHT	800 gm/sm (23.6 oz/sy) ± 5%
TOTAL WEIGHT	4700 gm/sm (120.9 oz/sy) ± 5%
BACKING MATERIAL	PVC □ Glass Fiber Spunbonded □ PVC
TILE SIZE	50 cm x 50 cm
TILES PER BOX	20 pcs


# Performance

---

FLOOR RADIANT PANEL	ASTM E-648
DIMENSION STABILITY	AACHEN Test & CNS 13924 □0.2%
FLAMMABILITY	BS 4790-1987: Hot Metal Nut, Method 1 Pass
LIGHT COLORFASTNESS	BS 1006 B02-1990, Grade 5 Pass
CROCKING COLORFASTNESS	BS EN ISO 105 X 12-1995 Pass
ELECTROSTATIC PROPENSITY	CNS 13595 10□2.0KV 20% R.H.,70F
SOIL RESISTANCE	3M Test Pass

All specifications are subject to normal manufacturing tolerances.

Recommended Installation Methods:



Quarter-turn

Brick