




**Armstrong**Flooring™

**ZENIT-CURDLEE®**






K866-203LM

Apricot




K866-202LM

Plume




K866-201LM

Light Beige




K866-204LM

Wood



K866-205LM


Plum



K866-007LM


Deep Tone






K866-005LM

Dawn Moon




K866-006LM

Rock




K866-003LM

Song of Moon




K866-004LM

Hazy Moon




K866-604LM

Tranquil




K866-601LM

Glacier



K866-605LM

Sunlit River



K866-602LM

Cirrus




K866-603LM

Blue Frog




K866-001LM Shadow




K866-002LM Clouds




K866-701LM Lavender




K866-702LM Pink Sakura




K866-703LM Sunkist




K866-501LM Willow Creek



K866-504LM Lime Green



K866-502LM Turquoise



K866-503LM Spring Grass



## Environmental Advantages



### Reliable Raw Materials

- Comply with REACH regulations
- Phthalate-free plasticizers
- Formaldehyde-free
- Comply with EN71-3, Migration of Certain Elements



### Life Cycle Assessment (LCA)

- Based on a comprehensive evaluation of the product's entire life cycle
- Environmental Product Declaration (EPD)
- EPD is an essential documentation to earn product credit for certifications like LEED and WELL, and it is a crucial criterion for selecting low-carbon, transparent materials.








### Low VOC Emissions for Improved Indoor Air Quality

- Agbb 28 day TVOC <math>< 10 \mu\text{g}/\text{m}^3</math>
- Formaldehyde-free
- FloorScore certified



## Technical Data

Characteristics	Standard	Unit	Result
Type of flooring	ISO 10581/EN 649		Polyurethane coated Homogeneous Sheet
Material			Polyvinyl chloride
Coating			TRUESHIELD XP
Safety criteria			
TVOC after 28 days	ISO 16000-6		< 10µg/m <sup>3</sup>
DOP Content	EN 14372		N.D.
Migration of Certain Elements	EN 71-3		Pass
Performance behaviour			
Roll width	ISO 24341/EN 426	m	2
Roll length	ISO 24341/EN 426	m	15/20
Overall thickness	ISO 24341/EN 428	mm	2.0
Dimensional stability	ISO 23999/EN 434	-	X (horizontal): 0.4% Y (vertical): 0.4%
Wear resistance	EN660-2/EN649	group	T
Chemical Resistance	ISO 26987/EN 423		Grade 0: No Stain
Color fastness	ISO 105-B02	rating	≥ 6
Static electrical charge	EN 1815	KV	≤ 2.0
Classification			
Domestic	EN 685	class	23 heavy duty
Commercial	EN 685	class	34 very heavy duty
Industrial	EN 685	class	43 heavy duty
Additional property			
Castor Chair  ✓	Underfloor Heating  ✓	Anti-bacteria  ✓	
Antistatic Behaviour  ✓	Chemical Resistance  ✓		



Website: [www.armstrongflooring.asia](http://www.armstrongflooring.asia)  
Hotline: 400-606-0866

YS-SF-ZENIT-CURDLEE® - 1124 - PRC Printed in China

The above information is for reference only. Our company reserves the right to modify the details mentioned at any time.  
For all contents in this manual, our company reserves all legal rights and final interpretation rights.

GRUPO COSMOS